

CLEANBOOT

BOOT



Coolmax® lining

Anti-slip sole



Fiber glass toe cap



EN ISO 20345 SAFETY FOOTWEAR

SB : Basic requirement (innocuousness, comfort, strength, resistance to shocks hazards & compression 200 J)

S1 : SB + closed back + A + E + FO

S1P : S1 + P

S2 : S1 + WRU

S3 : S2 + P + studded sole

MARKING

A : Antistatic footwear

AN : Ankle protection

CI : Insulation against cold

E : Energy absorption in the heel region

ESD : Electro Static Discharge

FO : Resistance to fuel oil of outsole

HI : Insulation against heat

M : Metatarsal protection

P : Penetration resistance

SRA : Slipping resistance on ceramic tile wet with dilute soap solution

SRB : Slipping resistance on smooth steel with glycerol

SRC = SRA + SRB

WR : Water resistant

WRU : Water resistant upper

HRO : Heat resistant outsole 300°C

Model	Item code	Standard	Marking	EUR Sizes	UK Sizes	US Sizes	Net weight/pair (kg) (42)
CLEANBOOT	RACB1	EN ISO 20345 2011	S2 SRC	39/47	5,5/12	6/12,5	1,1

SOLE

- Extra light PU dual density
- High performance grip: SRC rating

ENVIRONMENT

- Food industry
- Services & catering

UPPER

- Fiber glass toe cap 240J (20% more than the standard requirements): insulation from warmth & cold
- Very sturdy upper (2-2, 2mm), water & oil resistant, antibacterial
- Coolmax® lining: antibacterial, 100% ventilated & high water-absorbing capacity, high resistance to abrasion, foot-hygienic proof.

FOCUS

- Washable microfiber upper

