

# LIBERTINE WHITE COMPO



## EN ISO 20345 SAFETY FOOTWEAR

**SB** : Basic requirement (innocuousness, comfort, strength, resistance to shocks hazards & compression 200 J)  
**S1** : SB + closed back + A + E + FO  
**S1P** : S1 + P  
**S2** : S1 + WRU  
**S3** : S2 + P + studded sole

## MARKING

A : Antistatic footwear  
 AN : Ankle protection  
 CI : Insulation against cold  
 E : Energy absorption in the heel region  
 ESD : Electro Static Discharge  
 FO : Resistance to fuel oil of outsole  
 HI : Insulation against heat  
 M : Metatarsal protection  
 P : Penetration resistance  
 SRA : Slipping resistance on ceramic tile wet with dilute soap solution  
 SRB : Slipping resistance on smooth steel with glycerol  
 SRC = SRA + SRB  
 WR : Water resistant  
 WRU : Water resistant upper  
 HRO : Heat resistant outsole 300°C



Fiber glass toe cap



Model	Item code	Standard	Marking	EUR Sizes	UK Sizes	US Sizes	Net weight/pair (kg) (42)
LIBERTINE WHITE COMPO	BTAB1	EN ISO 20345 2011	SB WRU E A SRC	36/47	3,5/12	5,5/12	0,98

### SOLE

- Extra light PU dual density
- High performance grip: SRC rating

### ENVIRONMENT

- Food industry
- Services & catering

### UPPER

- Fiber glass toe cap 240J (20% more than the standard requirements): insulation from warmth & cold
- Washable microfiber
- Coolmax® lining: antibacterial, 100% ventilated & high water-absorbing capacity, high resistance to abrasion, foot-hygienic proof

### FOCUS

- The sizes 36-37 & 38 are specific to a women's foot shape.

