

MYCITY BLACK S3 SRC

CITYGRIP® range

100% full grain leather



High performance grip: SRC

EN ISO 20345 SAFETY FOOTWEAR

- SB** : Basic requirement (innocuousness, comfort, strength, resistance to shocks hazards & compression 200 J)
- S1** : SB + closed back + A + E + FO
- S1P** : S1 + P
- S2** : S1 + WRU
- S3** : S2 + P + studded sole

MARKING

- A : Antistatic footwear
- AN : Ankle protection
- CI : Insulation against cold
- E : Energy absorption in the heel region
- ESD : Electro Static Discharge
- FO : Resistance to fuel oil of outsole
- HI : Insulation against heat
- M : Metatarsal protection
- P : Penetration resistance
- SRA : Slipping resistance on ceramic tile wet with dilute soap solution
- SRB : Slipping resistance on smooth steel with glycerol
- SRC = SRA + SRB
- WR : Water resistant
- WRU : Water resistant upper
- HRO : Heat resistant outsole 300°C



RPU Polyurethan



Metal Free toecap 240J

Model	Item code	Standard	Marking	EUR Sizes	UK Sizes	US Sizes	Net weight/pair (kg) (42)
MYCITY BLACK	MCAN3	EN ISO 20345 2011	S3 SRC	39/47	5,5/12	6/12,5	1,09

SOLE

- Textile antiperforation midsole: Metal Free
- RPU Polyurethan
- High performance grip: SRC

ENVIRONMENT

- Industry, finishing construction
- Logistics

UPPER

- 240J fiberglass toecap : Metal Free
- Full grain leather
- Mesh 3D breathable lining

FOCUS

- High performance outsole with an outstanding grip capacity, very light, flexible & comfortable
- Outsole with innovative anti-abrasion material

